

# Dimensions Sheet

ITEM : POM Rod

Grade : NAT, BLK

두께(mm)	두께 허용범위(mm)		길이(mm)	무게(Kg)	길이(mm)	무게(Kg)
	최소	최대				
10	+0.1	+1.0	1000	0.11	3000	0.33
12	+0.1	+1.0	1000	0.16	3000	0.48
15	+0.1	+1.0	1000	0.25	3000	0.75
18	+0.1	+1.0	1000	0.36	3000	1.08
20	+0.1	+1.0	1000	0.45	3000	1.34
22	+0.1	+1.0	1000	0.54	3000	1.62
23	+0.1	+1.0	1000	0.59	3000	1.77
24	+0.1	+1.0	1000	0.64	3000	1.93
25	+0.1	+1.5	1000	0.70	3000	2.09
26	+0.1	+1.5	1000	0.75	3000	2.26
28	+0.1	+1.5	1000	0.87	3000	2.62
30	+0.1	+2.0	1000	1.00	3000	3.01
35	+0.1	+2.0	1000	1.37	3000	4.10
40	+0.2	+2.0	1000	1.78	3000	5.35
45	+0.2	+2.0	1000	2.26	3000	6.77
50	+0.2	+2.0	1000	2.79	3000	8.36
55	+0.2	+2.0	1000	3.37	3000	10.12
60	+0.2	+2.0	1000	4.01	3000	12.04
65	+0.2	+2.0	1000	4.71	3000	14.13
70	+0.2	+2.0	1000	5.46	3000	16.39
75	+0.2	+2.0	1000	6.27	3000	18.81
80	+0.2	+2.5	1000	7.13	3000	21.40
85	+0.2	+2.5	1000	8.05	3000	24.16
90	+0.2	+2.5	1000	9.03	3000	27.09
95	+0.2	+2.5	1000	10.06	3000	30.18
100	+0.5	+4.0	1000	11.15	3000	33.44
110	+0.5	+4.0	1000	13.49	3000	40.46
120	+0.5	+4.0	1000	16.05	3000	48.16
130	+0.5	+4.0	1000	18.84	3000	56.52
140	+0.5	+4.0	1000	21.85	3000	65.54
150	+1	+5.0	1000	25.08	3000	75.24
160	+1	+5.0	1000	28.54	3000	85.61
180	+1	+5.0	1000	36.12	3000	108.35
200	+1	+6.0	1000	44.59	3000	133.76
250	+1	+6.0	1000	69.67	3000	209.01

• 규격 외 제품 생산 및 문의는 당사로 연락 주십시오.

(주)일웅플라텍

서울특별시 구로구 구로중앙로42길 121 • Tel: 02-2632-5478 • Fax: 02-2634-3763 • E-mail: platech@platech.com • www.platech.com